



## LIGHT RING OPTION DATASHEET – P/N° 7V2475.1.1



Patent Pending

### PROTECTIVE MEASURES

- WATER RESISTANT
- IMPACT RESISTANT


### RECOMMENDATIONS

- TRAINING BY A QUALIFIED O & M INSTRUCTOR IS REQUIRED FOR SAFE USE.
- IF YOU PREFERRED TO GET THE LIGHT RING OPTION AS ADDITIONAL OPTION TO THE AUTOMATIC SWITCHED-ON SYSTEM, THEN A MAGNET HAS PREVIOUSLY BEEN PLACED INSIDE THE BLIND CANE. IN THIS SITUATION, THE LIGHT RING WILL WORK CORRECTLY ONLY IF INSTALLED FOLLOWING A SPECIFIC POLARITY. OTHERWISE, THE LIGHT RING'S PROXIMITY TO THE BLIND CANE'S MAGNET WOULD MAKE IT NOT WORK PROPERLY. TO IDENTIFY THE POLARITY, JUST PLACE THE LIGHT RING NEAR THE BLIND CANE'S MAGNET. IF THEY ATTRACT EACH OTHER, IT MEANS THIS ONE WILL BE THE RIGHT WAY THEY WILL KEEP WHEN THE LAST TWO SEGMENTS ARE PARALLEL. IF THEY REPUSE EACH OTHER, YOU NEED TO TURN THE LIGHT RING 180 DEGREES CLOCKWISE OR COUNTERCLOCKWISE.

### 1 OFF POSITION

#### Move

the ring towards the tip until it reaches the "magnet label".




**Rotate** the ring a quarter of round clockwise or counterclockwise keeping its ride until the label's thickness impedes the rotation.



### 2 ON POSITION

#### Move

the ring towards the handle until it reaches the rad band.



**Rotate** the ring a quarter of round clockwise or counterclockwise keeping its ride until the rad band's thickness impedes the rotation.



### CURIOSITIES

- THE LIGHT RING KIT REPRESENTS AN ADDITIONAL OR REPLACEMENT OPTION TO THE AUTOMATIC SWITCHED-ON SYSTEM WHOM NEEDS A MAGNET PLACED INSIDE THE BLIND CANE AFTER A RESIN REINFORCEMENT.
- THIS OPTION LETS YOU SWITCH MANUALLY ON AND OFF LETISMART LUCE JUST COURSING A RING UP AND DOWN FROM THE OFF POSITION (TOWARDS THE HANDLE) TO THE ON POSITION (TOWARDS THE TIP) AND VICEVERSA.



IP65



FS 559594